









Sync Reverser







Disc Brakes

State-of-the-art, powerful fuel efficient engine

TECHNICAL SPECIFICATIONS

ENGINE

Type : 36 HP (26.8 kW), 2800 RPM,

3 Cylinders, Inline FIP,

Coolant cooled with over flow reservoir, Naturally aspirated

Air filter : Dry type, dual element

TRANSMISSION

Clutch : Single dry type : 8 Forward + 8 Reverse Gear box

Sync Reverser

: Forward: 1.9 - 22.7 kmph Speeds

Reverse: 1.7 - 23.7 kmph

BRAKES

: Oil Immersed Disc Brakes

HYDRAULICS

Maximum Lifting capacity: 910 kgf

STEERING

Dual PTO

Type : Power

POWER TAKE OFF

: Independent, 6 Splines Type

> : 540 @ 2500 ERPM 540 @ 1925 ERPM

WHEELS AND TYRES

: 8.0 x 16 (0.20 x 0.40 m), 4 PR Front

Rear : 12.4 x 24.4 (0.31 x 0.62 m), 4 PR,

HLD

FUEL TANK

: 39 L Capacity

ELECTRICAL SYSTEM

: 52 Ah, 12 V battery, 43 Amp. alternator,

12 V. 1.2 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 1295 kg Wheel base : 1574 mm Overall length : 2919 mm Overall width : 1455 mm

Ground clearance : 0388 mm Turning radius with brakes : 2600 mm

ACCESSORIES

· Ballast weights · Trailer brake kit

FACTORY FITTED OPTIONS

Roll over protection structure (ROPS)

· Seat with seat belt

FEATURES

- Sync reverser Finger guard FNR NSS PTO NSS
- Underhood with up draft exhaust muffler
- Water separator Digital hour meter
- Radiator screen Metal face seals for front and rear axle.

Note: All the options / features may not be available in a single variant.









Side shift control levers



Stylish, Skip free Power Steering



Smart Brakes

John Deere **Genuine Parts**

I Economical I Reliable I I Easily available I



John Deere India Private Limited


3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.









• Harvesters • Finance

