







Power steering



Single piece hood with lock





TECHNICAL SPECIFICATIONS

ENGINE

Type : John Deere 3029D, 46 HP (34.1 kW),

2100 RPM, 3 Cylinders, Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift Speeds : Forward 2.83 - 30.92 kmph

Reverse 3.71 - 13.43 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

Maximum Lifting

capacity : 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM Economy : 540 @ 1600 ERPM

WHEELS AND TYRES

Front : 8.0 x 18 (0.20 x 0.46 m), 8 PR Rear (Standerd) : 13.6 x 28 (0.34 x 0.71 m), 12 PR

(Optional) : 14.9 x 28 (0.38 x 0.71 m), 12 PR

FUEL TANK

Capacity : 60 L

ELECTRICAL SYSTEM

: 88 Ah, 12 V battery, 40 Amp. alternator, 12 V, 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

Total weight : 2100 kg
Wheel base : 1950 mm
Overall length : 3370 mm
Overall width : 1810 mm
Ground clearance : 0360 mm
Turning radius with brakes : 2900 mm

ACCESSORIES*

• Ballast weights • Canopy • Canopy holder

• Draw bar • Tow hook • Wagon hitch

FACTORY FITTED OPTIONS

• JDLllllx[™] (Alerts, Monitoring and Tracking System)

Reverse PTO

 Roll over protection structure (ROPS) with deluxe seat and seat belt

Mechanical quick raise and lower (MQRL)

Selective control valve (SCV)

FEATURES

• Collarshift type gear box • Finger guard • PTO NSS

• Underhood exhaust muffler • Water separator

Single piece hood opening with gas struts

2WD model is also available

Note: All the options / features may not be available in a single variant.



Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve

Ideal for heavy load applications

High torque across the operating speed range

Rear oiled axle with metal face seal



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



Top Shaft Lubrication

John Deere Genuine Parts

I Economical I Reliable I Easily available I



John Deere India Private Limited


3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.









Harvesters • Finance

