







Mobile Charging Point with Holder



Hood Lock



Planetary Gear with Straight Axle





Technical Specifications

ENGINE	
Туре	: John Deere 3029D, 50 HP (37.2 kW), 2100 RPM, 3 Cylinders,
	Coolant cooled with everflow

Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift : Forward 2.97 - 32.44 kmph Speeds Reverse 3.89 - 14.1 kmph

BRAKES

: Oil immersed disc brakes

HYDRAULICS

TRANSMISSION

Maximum Lifting capacity: 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

STEERING

Type : Power

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM **Economy** : 540 @ 1600 ERPM

WHEELS AND TYRES

Front : 8.0 x 18 (0.20 x 0.46 m), 8 PR Rear : 14.9 x 28 (0.38 x 0.71 m), 12 PR

FUEL TANK

: 60 L Capacity

ELECTRICAL SYSTEM

: 88 Ah. 12 V batterv 40 Amp. Alternator 12 V. 2.5 kW Starter motor

DIMENSIONS AND WEIGHT

: 2010 kg Total weight : 1970 mm Wheel base Overall length : 3430 mm : 1830 mm Overall width Ground clearance : 0430 mm Turning radius with brakes: 2900 mm

ACCESSORIES*

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

FACTORY FITTED OPTIONS

- Jollink™ (Alerts, Monitoring and Tracking System)
- Roll over protection system (ROPS) with deluxe seat and seat belt
- Mechanical guick raise and lower (MQRL)
- Selective control valve (SCV) Dual PTO

FEATURES

- Collarshift type gear box Finger guard PTO NSS
- Digital Hour Meter Underhood exhaust muffler
- Water separator

2WD model is also available

Note: All the options / features may not be available in a single variant.

New 50 HP 4WD 372 Model 5050 D

Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve

Ideal for heavy load applications

High torque across the operating speed range



Dry Type Air Filter



Oil Jet for Piston Cooling



Radiator with **Overflow Reservoir**



5050 D 4WD 00 0120 ENG

Top Shaft Lubrication

John Deere **Genuine Parts**

I Economical I Reliable I Easily available I



John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.







