



Tilt Steering For operator comfort adjustable up to 25° tilt, with lock latch



Easy hitching and usage of implement through EQRL switches



Smart Brakes Self adjusting, self equalising, hydraulically actuated, oil immersed disc brakes



Hood Lock Mobile Charging Point with Holder





LCD Panel

• Hour Meter

• Trip Meter

MFD

Multi Function Display

Single piece

hood opening

Ease in opening

Climbing up and

down the tractor

is now easier

Side bar &

steps

with gas struts



High torque More productivity 5065 E 00 0819 ENG

John Deere **Genuine Parts**

Finger guard

Enhanced safety

Go Home

Reach home

safely in the

Feature

I Economical I Reliable I I Easily available I



FUEL TANK CAPACITY : 68 L

ELECTRICAL SYSTEM

88 Ah. 12 volt batterv 40 Amp, alternator 12 Volt, 2.5 kW Starter New

65 HP 48.5 kW

Model 5065 E

motor

DIMENSIONS AND WEIGHT

: 2290 kg Total weight Wheel base : 2050 mm Overall length : 3535 mm Overall width : 1890 mm : 0510 mm Ground clearance Turning radius with brakes : 3099 mm

OPTIONAL ACCESSORIES*

- Ballast weights Canopy Drawbar
- Wagon Hitch Canopy holder

ADDITIONAL FEATURES

- International look
- · Exhaust muffler quard
- Car type engine ON/OFF
- Radiator with over flow reservoir
- Water bottle holder
- Mobile charging point with holder

OPTIONS

Creeper speeds

FACTORY FITTED OPTIONS

 Roll over protection sturcture (ROPS) with deluxe seat and seat belt

Model also available in MFWD

Note: Some of the options may not be available in all combinations. For variants please check with your nearest dealer.

HYDRAULICS

ENGINE

Type

Air filter

Clutch

Gear Box

BRAKES

Speeds

TRANSMISSION

Maximum Lifting capacity: 2000 kgf 3 Point linkage : Category II

Automatic depth & draft control

: 65 HP (48.5 kW), 2400 RPM,

3 cylinder Direct injection,

Turbo charged, Rotary F.I.P.,

liquid cooled with overflow

: Dry type, dual element

: 9 Forward + 3 Reverse

: Forward 2.6 to 31.2 kmph

: Self adjusting, Self equalising,

Reverse 3.7 to 24 kmph

Hydraulically actuated,

Oil immersed disk brakes

reservoir

: Collar Shift

(ADDC)

STEERING

Type : Power

Steering Column : Tiltable up to 25° with lock latch

FRONT EXLE

Heavy duty variable track

POWER TAKE OFF

: Independent, 6 splines Type

Dual PTO

RPM : 540 @ 2376 ERPM (Standard)

540 @ 1705 ERPM (Economy)

WHEELS AND TYRES

: 6.5 x 20 (0.17 x 0.51 m), 8 PR Front : 18.4 x 30 (0.47 x 0.76 m), 8 PR Rear

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.









• Harvesters • Finance

