







Front Visibility



Smart 3D Seat



Side Shift Gears



International Looks (Automatic hood with lock)





Type : John Deere 3029D,

40 HP (29.8 kW),

2100 RPM, Coolant cooled with overflow reservoir, Naturally aspirated

Air filter : Dry type, Dual element

TRANSMISSION

Clutch : Single / Dual

Gear box : 8 Forward + 4 Reverse, Collarshift
Speeds : Forward 2.83 - 31.07 kmph
Reverse 3.74 - 13.52 kmph

HYDRAULICS

Maximum Lifting capacity: 1600 kgf 3 point linkage : Category - II

Automatic depth and draft control

(ADDC)

POWER TAKE OFF

Type : Independent, 6 Splines Standard : 540 @ 2100 ERPM

WHEELS AND TYRES

Front : 6.0 x 16 (0.15 x 0.41 m), 8 PR Rear : 13.6 x 28 (0.34 x 0.71 m), 12 PR

FUEL TANK

Capacity : 60 L

ACCESSORIES*

- Ballast weights Canopy Canopy holder
- Draw bar Tow hook Wagon hitch

FACTORY FITTED OPTIONS

Roll over protection structure (ROPS)
 with deluxe seat and seat belt



FEATURES

- PTO NSS Underhood exhaust muffler
- Water separator
- Rear oil axle with metal face seal

Modern, technologically advanced, powerful John Deere 3029D engine

Wet liner

Long life and less maintenance

High torque reserve

Ideal for heavy load applications

 High torque across the operating speed range





Planetary Gear with Straight Axle



Digital Hour Meter



ter Finger Guard



Oil Jet for Piston Cooling



Radiator with Overflow Reservoir



vith Top Shaft ervoir Lubrication



Dry Type Air Filter



Battery Inside Hood



Oil Immersed Disc Brakes

John Deere Genuine Parts

I Economical I Reliable I Easily available I



John Deere India Private Limited


3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra | www.JohnDeere.co.in











• Harvesters • Finance

