















Wheat

Soybean

## **TECHNICAL SPECIFICATIONS**

Engine		John Deere 4039, 100 HP (74 kW), 2100 RPM, 4 cylinder, turbo charged engine
Pre Cleaner & Air Cleaner		Dry type
Cooling System		Coolant
Cutter Bar Width (mm)		4170
Threshing System		Rasp bar and spike tooth
Cylinder (WxD) (mm)		Rasp bar - 1020 x 610, Spike tooth - 1010 x 585
Separation Type		Straw walker with 8 wing beater and beater grate
Cleaning Area (m²)		2.45
Grain Tank Storage Capacity (m³)		2.7
Transmission		Mechanical combination of synchronizer and constant mesh spur gears with differential unit 4 Forward + 2 Reverse
Brakes		Hydraulically actuated, Oil immersed disc brakes
Clutch Type		Dry Fiction Disc
Tyre Size	Front	16.9 x 30 (0.43 x 0.76 m), 12 PR
	Rear	7.5 x 16 (0.19 x 0.41 m), 12 PR
Fuel Tank Capacity (L)		240
Total Weight Without Grain (kg)		7500
<b>Dimensions (Harvesting)</b> L×W×H (mm)		8175 x 5945 x 3715
Ground Clearance (mm)		~ 360
Crops		Paddy, Wheat, Soybean, Cluster Bean, Corn Pigeon Peas, Chick Peas, Black Gram, Sorghum, Pearl Millet, Finger Millet, Mustard, Peas, Barley, Sunflower, Coriander
Factory Fitted Options		<b>JoLink</b> ™ (Alerts, Monitoring and Tracking System)
		Straw Management System

Combine Harvester Model W50 Synchrosmart is also available.



## **SALIENT FEATURES**



**Posi Torque Drive** 



**Self Cleaning Radiator** 



**Light Weight Machine** 



Electrically Operated
Header Reel Speed Adjustment



6 Bat Reel



**Beater and Beater Grate** 



Adjustable Cutter Bar



Tilt Steering and Adjustable Operator Seat



Adjustable Floating
Drum Type Feeder House



Straw Management System<sup>#</sup>



Neutral start and Park brake alert

## John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. www.JohnDeere.co.in

For more information, please contact our authorised dealer or nearest area office.







• Harvesters • Finance

