

Specially designed for **John Deere 5000 series** tractors



TECHNICAL SPECIFICATIONS

Model	Unit	PD0709	PD0712	PD0718	PD0724
Frame		Heavy Duty Rectangular pipe			
Hitch Type		Cat-II			
Gear Box		Single speed gear box, with 3:1 ratio			
PT0		Regular, 540 RPM			
Auger length	inch	43			
	mm	1092			
Auger diameter	inch	9	12	18	24
	mm	228	305	457	610
Suitable Tractor Rating	HP	36-40	40-45	45-50	50-55
	kW	26.8 - 29.8	29.8 - 34.1	34.1 - 37.3	37.3 - 41.0
Weight (without PTO shaft)	kg	218	225	236	260





Fit and Finish Design

Robust structure designed for easy and quick attachment to tractor and transportation.

(Optional attachment for parking stand)



Replaceable Auger

With 6 mm thick, wear resistant plate. The auger is available in 4 different diameter sizes.



Robust Gear Box

Robust and highly efficient single speed gear box which requires less maintenance and repair cost.



Replaceable Blades

Strong, easy to replace blades made with boron steel material



Operator Safety

Safety covers on gear box and PTO drive shaft that protects the operator from moving parts.



Auger Point

Auger point tip is made of boron steel material for ease of penetration in hard soil.

POST HOLE DIGGER 01 0919 ENG LPB

John Deere India Private Limited

3rd floor, Tower-15, Cybercity, Magarpatta City, Hadapsar, Pune - 411013. Maharashtra. | www.JohnDeere.co.in







